



## 3103 - WETLOOK ACRYLIC SEALER

861 Derwent Way, Delta, BC, Canada V3M 5R4  
Telephone 604 -522 -2811 Facsimile 604 522-5141

### PRODUCT BULLETIN

#### General Description

3103 is a clear, highgloss penetrating type concrete and masonry sealer based on specially formulated aqueous acrylic that will not yellow with exterior exposure. This coating is outstanding in its ability to protect surfaces from staining and discoloration.

#### Uses

Exterior - Very effective on exposed aggregate, concrete or concrete pavers to achieve the "wet" look and to minimize discoloration caused by the rough texture, trapping dirt particles. Excellent all round weather proofing coating.

Interior - Floor sealer and dust proofer. Protective coating for concrete and other substrates against occasional spills of acids, alkalis, food acids, oil, water based paints, wet concrete, etc. Pleasant light smell while wet.

#### Physical Properties

Appearance	-	Milky white liquid – dries clear
Density (25°C)	-	1.04 kg/litre (8.7 lb/U.S. gallon)
Dry Film Appearance	-	Clear
Drying Time (21°C)	-	1 - 2 hours
Coverage	-	200 - 330 square feet per U.S. gallon

#### Application Instructions

Make sure surface is free of oil and dirt. This can be achieved by scrubbing with a soap solution of trisodium phosphate (TSP) or a mild acid solution. After cleaning, rinse the surface thoroughly and let dry. Apply IM 3103 by spray, brush or roller. Apply above 10°C (50°F). Substrate must be free of moisture. New concrete must have cured for 14 days.

#### Clean Up

Tools can be cleaned up with water after use.

#### Packaging

Available in 4 litre (1 gallon), 20 litre (5 gallon), and 205 litre (55 gallon) containers.